
F44P



GLOBAL TRUSS F44P TRUSS SYSTEM

Global Truss represents the highest quality and reliability.

The Global Truss F44P is a 4-point truss system. This provides optimum volume and carrying capacity for its construction size and a tube diameter of only 50mm. This system is connected via a special conical connector system, which is joined together to a complete form fit by means of a copper hammer, creating optimal traction.

The Global Truss F44P finds application in trade fairs and shops, as well as in the event industry in general. It is also characterised by a minimum transport volume and the special lightweight design.

The conical connectors are of course included in the scope of delivery - special designs and powder coatings can be carried out at short notice.

Global Truss has the largest truss storage worldwideand is permanently able to deliver all systems. Furthermore, Global Truss is the only truss manufacturer with its own coupler and hook range tested by "TÜV" and "DIN".

TÜV NORD – TÜV NORD CERT GmbH – Baumuster geprüft

TECHNICAL DATA

Pipe diameter main pipe:	50mm
Wall thickness:	3mm
Material:	AlMgSi F31 / T6082
Pipe diameter brace:	20mm

Conical connectors included in scope of delivery

PRODUZIERT NACH DEUTSCHER INDUSTRIENORM – DIN 4113 – DIN V 4113-3 – DIN EN 13814 (DIN 4112)


INCLUSIVE

4 X



8 X





LOAD TABLE

Span	Uniform distribution load	Deflection	Center point load	Deflection	point load in third-point	Deflection	point load in quarter-point	Deflection	point load in fifth-point	Deflection
m	kg / m	cm	kg	cm	kg	cm	kg	cm	kg	cm
1,00	1332,3	-	811,6	-	794,6	-	762,7	-	744,3	-
2,00	1150,7	0,3	762,7	-	733,3	0,4	680,7	0,3	652,0	0,3
3,00	937,7	0,5	719,4	0,3	680,7	0,7	614,5	0,5	580,0	0,5
4,00	731,0	0,7	680,7	0,5	635,2	0,9	560,3	0,6	522,4	0,6
5,00	465,0	1,0	645,9	0,6	595,4	1,2	514,7	0,8	475,2	0,9
6,00	320,0	1,5	614,6	0,8	560,3	1,6	476,0	1,1	399,0	1,1
7,00	233,3	2,0	586,2	1,1	529,1	2,0	408,3	1,5	338,9	1,6
8,00	176,8	2,5	560,3	1,6	501,1	2,4	353,5	2,0	293,4	2,0
9,00	138,0	3,1	536,5	2,1	465,7	3,5	310,4	2,4	257,7	2,5
10,00	110,2	3,7	514,7	2,8	413,4	3,9	275,6	2,9	228,7	3,1
11,00	89,7	4,5	493,5	3,6	370,1	4,6	246,7	3,6	204,8	3,6
12,00	74,1	5,6	444,7	4,2	333,5	5,4	222,3	4,1	184,5	4,3
13,00	62,0	6,8	402,7	4,9	302,8	6,3	201,4	4,8	167,1	5,0
14,00	52,3	7,9	366,3	5,5	274,7	7,1	183,1	5,4	152,0	5,7
15,00	44,6	8,6	334,1	6,2	250,6	8,1	167,1	6,0	138,7	6,4
16,00	38,2	9,0	305,5	6,9	229,1	10,4	152,8	6,8	126,8	7,1
17,00	32,9	10,0	279,8	7,6	209,8	11,5	139,9	7,4	116,1	7,7
18,00	28,5	10,7	256,4	8,4	192,3	12,6	128,2	8,2	106,4	8,5

The weight of the truss is considered in the load table.

Technical changes and errors are reserved

Available on the App Store

Become a Fan on Facebook
facebook.com/GlobalTruss

Visit the official Global Truss website:
www.GlobalTruss.de